



SIZE	FLOW RANGE GPM (m ³ /hr)	INLET/ OUTLET	DIMENSIONS Inches/(mm)					PURGE	AUX. PURGE	CLEANOUT DOOR Inches (mm)	UTILITY PORT	GAUGE PORT	AIR VENT PORT				
			A	B	C	D	E										
3T	115-280 (26-63)	3" Grooved	35-3/8 (899)	26-1/4 (667)	2-1/4 (57)	10-1/2 (267)	N/A	1" FNPT		3x4 (76x102)							
4T	190-450 (43-102)	4" Grooved	52-1/8 (1324)	42-3/4 (1086)	2-7/8 (73)	11 (279)	10 (254)	1-1/2" FNPT	3/4" FNPT	4x6 (102x152)	3/4" FNPT	1/4" FNPT					
5T	310-710 (70-161)	5" Grooved	59-1/2 (1511)	49 (1245)	3-5/16 (84)	12 (305)											
6T	440-1200 (100-272)	6" Grooved	65-1/2 (1664)	54-3/4 (1391)	3-7/16 (87)	13 (330)		2" FNPT	1" FNPT					6x8 (152x203)			1/2" FNPT
8T	790-1800 (179-408)	8" Grooved	79-1/2 (2019)	67-1/8 (1705)	4-7/16 (113)	15 (381)											
10T	1250-2800 (284-636)	10" Grooved	93-1/2 (2375)	80-1/8 (2035)	5-3/8 (137)	17 (432)	12 (305)										
12T	1750-3900 (397-885)	12" Grooved	109-3/8 (2778)	94-5/8 (2403)	6-3/8 (162)	18 (457)											
14T	2400-5000 (545-1135)	14" Grooved	CONSULT FACTORY														
16T	3300-6800 (749-1544)	16" Grooved															
18T	4000-8200 (908-1861)	18" Grooved															
20T	6100-12000 (1385-2724)	20" Grooved															

SHIPPING WEIGHT				
	3T	4T	5T	6T
Lbs.	110	250	270	335
Kg.	50	113	122	152
	8T	10T	12T	14T
Lbs.	500	760	1070	1215
Kg.	227	345	485	551
	16T	18T	20T	
Lbs.	1500	1710	2200	
Kg.	680	776	998	

OPTIONS: (See Reverse Side for Model Configuration Matrix)

- Stainless Steel
 - Non-Std. Press. Requirements
 - Low Profile
- (Consult Factory)

