



SYSTEM MODEL		GLS-1200-HH	CSS-1200-HH
	Design Flow Rate, GPM	2900@40 TDH *	2900@80 TDH *
Item 1	Separator Model	CS-12T-FLG Carbon Steel, Powder Coated	
Item 2	Frame Construction	Carbon Steel, Powder Coated	
Item 3	Pipe Assembly	Carbon Steel, Rust Inhibitor Primer with Enamel Finish	
MOTOR 460 VAC TEFC			
Item 4	Horsepower	40 hp	75 hp
	Approximate Amps @ 460V	52 amps	96 amps
	RPM	1150	1750
PUMP			
Item 5	Pump Casing	Cast Iron	
	Pump Impeller	Bronze	
	Std. Mechanical Seal	VITON Elastomer, Silicon Carbide Seat, Carbon Rotary	
STRAINER (Optional)		Basket	Y-Strainer
Item 6	Body Construction	Cast Iron	
	Internal Screen	1/4" Perforated 304 Stainless Steel	
	Connection Type	Class 150 Flange	
CONTROL PANEL (UL listed and labeled, manufactured to UL-508A Std.)			
Item 7	Enclosure	NEMA 4 Powder Coated, Watertight, UL listed and CSA approved	
	Electrical Components	Disconnect Starter with Thermal Overload, HOA, 460/120 Transformer with Circuit Breakers, Pump "RUN" Light, Lockable Door Disconnect, Magnetic Contactor, Purge Timer, Manufactured with all UL listed & CSA approved electrical components.	
PURGE VALVE (Requires Power to Open and Power to Close. Must Close Manually if Open During a Power Outage)			
Item 8	Actuator, Motorized	120 VAC 60Hz	
	Connection Type	2" Female NPT, Ball Valve	
SPECIFICATIONS			
	Dim "A"	109-3/8"	
	Dim "B"	68-1/2"	59-1/16"
	Dim "C"	106"	37"
	Max. Inlet P.S.I.	100	
	Max. Operating P.S.I.	150	
	Max. Operating Temp.	120°F	
	Inlet (Class 150 Flange)	12"	10"
	Outlet (Class 150 Flange)	12"	
	Shipping Weight	5500 Lbs	4900 Lbs

* Component Arrangement May Vary from Drawing

Note: Dimensions are approximate and are for reference only. Dimensions subject to change without notice. Weights are approximate.

Section 5, Page 16

REV. 7/11