



SYSTEM MODEL		TSS-B-500-HH	TSS-B-501-HH	TSS-B-500-LH	TSS-B-501-LH
	Design Flow Rate, GPM	510@80 TDH	650@80 TDH	510@40 TDH	650@40 TDH
Item 1	Separator Model	CS-5T-FLG Carbon Steel, Powder Coated			
Item 2	Frame Construction	Carbon Steel, Powder Coated			
Item 3	Pipe Assembly	Schedule 80 PVC with Enamel Finish*			
Item 4	SBC Model	SBC-5000			
Item 5	Conductivity Meter	(SEE SECTION 12)			
<b>MOTOR 460 VAC TEFC</b>					
	Horsepower	20 hp		10 hp	15 hp
Item 6	Approximate Amps @ 460V	27 amps		14 amps	21 amps
	RPM	3500	1750	3500	1750
<b>PUMP</b>					
	Pump Casing	Cast Iron			
Item 7	Pump Impeller	Bronze			
	Std.Mechanical Seal	VITON Elastomer, Silicon Carbide Seat, Carbon Rotary			
<b>BASKET STRAINER (Standard)</b>					
	Body Construction	Cast Iron			
Item 8	Internal Screen	1/4" Perforated 304 Stainless Steel			
	Connection Type	Class 150 FLG			
<b>CONTROL PANEL (UL listed and labeled, manufactured to UL-508A Std.)</b>					
	Enclosure	NEMA 4 Powder Coated, Watertight, UL listed and CSA approved			
Item 9	Electrical Components	Starter with Thermal Overload, HOA, 460/120 Transformer with Circuit Breakers, Pump "RUN" Light, Lockable Door Disconnect, Magnetic Contactor, Manufactured with all UL listed & CSA approved electrical components.			
	Service Light (Standard)	25 Watt, Amber, 120 VAC			
<b>RECOVERY TANK</b>					
	Body Construction	304 Stainless Steel			
Item 10	Internal Screen	304 Stainless Steel			
	Filter Bag	25 Micron Polypropylene			
	Differential Press. Switch	Dial Indicator with Dry N.O. Contact			
<b>PURGE VALVE</b>					
	Actuator, Motorized	120 VAC 60Hz			
Item 11	Connection type	1-1/2" Female NPT, Ball Valve			
<b>SPECIFICATIONS</b>					
	Dim "A"	93"			
	Dim "B"	36"			
	Dim "C"	36"			
	Max. Inlet P.S.I.	100			
	Max. Operating P.S.I.	150			
	Max. Operating Temp.	100°F			
	Inlet (Class 150 FLG.)	4"	6"		5"
	Outlet (Class 150 FLG.)	5"			
	Shipping Weight	1304 Lbs			

Note: Dimensions are approximate and are for reference only. Dimensions subject to change without notice. Weights are approximate.  
 \* Optional or as required by temperature/pressure requirements---Carbon Steel, Rust Inhibitor Primer with Enamel finish